



Order No. L6.51950 Balancing Rope with Holding Rope

Play value

Our hanging ropes turn simple rope structures into exciting accesses and crossings. The playful challenge of maintaining balance attracts younger and older children alike. With a combination of walking and handrail rope, the balancing rope with holding rope ensures secure footing and helps to maintain balance. Imaginative artistic movements can be tried out on the double hanging rope. Depending on individual planning, the units can be extended with additional elements.

Fundamental characteristics

- Child-friendly challenge
- Incentive for playing: balancing, role-playing game
- Movement: balance, coordination

Recommended for

- School children
- Young people
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar




Order No. 6.51900 Double Hanging Rope, Photo © Monica Bedmar

**Double Hanging Rope
Balancing Rope with Holding Rope**




Order No. L6.51950 Balancing Rope with Holding Rope



L6.51900



L6.51950



Safety check according to DIN EN 1176

Components

Order No. L6.51900 Double Hanging Rope
 4 Support frames with steel feet
 2 Ropes


Order No. L6.51950 Balancing Rope with Holding Rope
 2 Support frames with steel feet
 2 Ropes

Installation information

Surfacing requirements corresponding to a fall height of
Order No. L6.51900 ≤ 2.00 m
Order No. L6.51950 ≤ 0.60 m
 (please refer to price list for more detailed information)

Foundations
Order No. L6.51900
 2 items 60 x 110 x 60 cm
 Excavation depth 80 cm
Order No. L6.51950
 2 items 60 x 60 x 60 cm
 Excavation depth 80 cm

Attention:
Exact measurements may vary;
for all installation dimensions refer to current assembly instructions.
 Technical changes reserved.



L6.51900



L6.51950

Technical information

Equipment made of non-impregnated mountain larch

Peeled white
 Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Bevel cut
 Vertical stand posts with bevelled end grain section as constructive wood preservation measure



Richter Hercules type rope
 Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing



Aluminium rope pressing
 Aluminium rope pressing, cylindrically pressed, with rounded ends



Rope connection fixed
 Fixed rope connection without dangerous openings. Screw connection adjustable and countersunk in the wood



Profiled washer
 Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



Adjustable
 Adjustable two-piece bolt connection, easy to maintain, no projecting threads



Ground anchor
 All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



For more detailed explanation of the quality characteristics see price list.

Dimensions
 (small deviations possible)

Order No. L6.51900 Double Hanging Rope
 Height 2.45 m
 Attachment height 2.05 m
 Length 3.25 m
 Weight 180 kg

Order No. L6.51950 Balancing Rope with Holding Rope
 Height 1.90 m
 Height of walking ropes 0.40 m
 Height of holding ropes 1.70 m
 Length 3.25 m
 Weight 100 kg